

230V IP65 LED Floodlights 4000K



MLA part code	FLR10	FLR20	FLR30	FLR50
Description	230V IP65 LED Floodlight			
Finish	Black			
Nett weight (kg)	0.48	0.622	0.975	1.458
Wattage (W)	10	20	30	50
Lumens	800 ± 5%	1600 ± 5%	2400 ± 5%	4000 ± 5%
Efficacy (lm/W)	87	85	82	83
Dimensions (mm)	Height – 105 Width – 130 Projection – 53	Height – 125 Width – 150 Projection – 53	Height – 160 Width – 185 Projection – 63	Height – 205 Width – 225 Projection – 63
Beam angle	100°	105°	110°	
CCT	4000K			
LED Colour	Cool White			
CRI	>80			
Running current (A)	0.07	0.16	0.13	0.22
P.F	0.565	0.534	0.974	0.974
Life span (Hrs)	25,000			
Input voltage	Mains 230V 50Hz			
Construction	Die-cast aluminium			
Class	Class I			
IP rating	IP65			
Warranty	3 Years			
Dimmable	No			
Origin of Manufacture	China			
Declaration of Conformity (held on file)	Yes			
Manufactured in accordance with	BS EN 60598			
EAN	5055832986706	5055832986720	5055832986744	5055832986768

