

230V LED CCT Emergency Batten



| MLA part code | BATC4EM | BATC5EM | BATC6EM |
|--|--|---|---|
| Description | 230V 4ft LED CCT Emergency Batten | 230V 5ft LED CCT Emergency Batten | 230V 6ft LED CCT Emergency Batten |
| Finish | White | | |
| Nett weight (kg) | 1.45 | 1.85 | 2.1 |
| Dimensions (mm) | Length – 1170 Height – 71 Width - 61 | Length – 1470 Height – 71 Width - 61 | Length – 1734 Height – 71 Width - 61 |
| Wattage (W) | 22 | 35 | 40 |
| Lumens (lm) | 3000K – 2545 ± 5% 4000K – 2765 ± 5% 6000K – 2745 ± 5% | 3000K – 3775 ± 5% 4000K – 4160 ± 5% 6000K – 4160 ± 5% | 3000K – 4645 ± 5% 4000K – 5045 ± 5% 6000K – 4955 ± 5% |
| Efficacy (lm/W) | 3000K - 112 4000K – 129 6000K – 120 | 3000K - 106 4000K – 126 6000K – 117 | 3000K - 116 4000K – 129 6000K – 123 |
| Lumens emergency mode (lm) | 3000K – 205 ± 5% 4000K – 210 ± 5% 6000K – 220 ± 5% | 3000K – 205 ± 5% 4000K – 205 ± 5% 6000K – 220 ± 5% | 3000K – 200 ± 5% 4000K – 210 ± 5% 6000K – 210 ± 5% |
| CCT | 3000K - Warm white 4000K - Cool white 6000K - Daylight | | |
| CRI | >80 | | |
| Battery type | Li-Ion 6.4V 9.6Wh 1500mAh | | |
| Running current (A) | 0.1 | 0.15 | 0.18 |
| Inrush current | 40A | | |
| Power factor | 0.96 | 0.97 | 0.97 |
| Beam angle | 137° | | |
| Life span (Hrs) | 50,000 | | |
| Input voltage | Mains 230V 50Hz | | |
| Construction | Steel & Polycarbonate | | |
| Class | Class I | | |
| IP rating | IP20 | | |
| Dimmable | No | | |
| Warranty | 5 Years (Battery 1 Year) | | |
| Origin of Manufacture | China | | |
| Declaration of Conformity (held on file) | Yes | | |
| Manufactured in accordance with | BS EN 60598 | | |
| EAN | 5055832994114 | 5055832994138 | 5055832994176 |

