

DATA SPECIFICATION SHEET



Linkable Switched Slimline Fluorescent Fitting

MLA Accessories Code	T56	T58	T514	T521	T528	T535
Description	T5 6Watt Fluorescent Fitting	T5 8Watt Fluorescent Fitting	T5 14Watt Fluorescent Fitting	T5 21Watt Fluorescent Fitting	T5 28Watt Fluorescent Fitting	T5 35Watt Fluorescent Fitting
Finishes available	White	White	White	White	White	White
Overall Dimensions (mm) Height – Width - Length	(H)43mm (W)22.5mm A=(L)267mm	(H)43mm (W)22.5mm A=(L)343mm	(H)43mm (W)22.5mm A=(L)604mm	(H)43mm (W)22.5mm A=(L)904mm	(H)43mm (W)22.5mm A=(L)1204mm	(H)43mm (W)22.5mm A=(L)mm
Diffuser Dimensions (mm) Height – Width - Length	(H)22mm (W)22.5mm (L)226mm	(H)22mm (W)22.5mm (L)302mm	(H)22mm (W)22.5mm (L)563mm	(H)22mm (W)22.5mm (L)863mm	(H)22mm (W)22.5mm (L)1163mm	(H)22mm (W)22.5mm (L)mm
Recommended location	Indoor	Indoor	Indoor	Indoor	Indoor	Indoor
Weight	0.141kg	0.167kg	0.256kg	0.362kg	0.457kg	0.512kg
Lamp Supplied	Yes T5 3500K	Yes T5 3500K	Yes T5 3500K	Yes T5 3500K	Yes T5 3500K	Yes T5 3500K
Lamp Life (hours)	10,000	10,000	10,000	10,000	10,000	10,000
Voltage (V)	220-240V 50Hz	220-240V 50Hz	220-240V 50Hz	220-240V 50Hz	220-240V 50Hz	220-240V 50Hz
Running current (I)	30MA	33MA	58MA	87MA	126MA	150MA
Class	Class II	Class II	Class II	Class II	Class II	Class II
IP	IP20	IP20	IP20	IP20	IP20	IP20
Linkable (Maximum Number)	Direct or cable (40)	Direct or cable (40)	Direct or cable (20)	Direct or cable (15)	Direct or cable (10)	Direct or cable (8)
Photometric Testing	Not available	Not available	Not available	Not available	Not available	Not available
Instruction sheet	Yes	Yes	Yes	Yes	Yes	Yes
Origin of manufacture	China	China	China	China	China	China
Main materials:	Polycarbonate Self extinguishing	Polycarbonate Self extinguishing	Polycarbonate Self extinguishing	Polycarbonate Self extinguishing	Polycarbonate Self extinguishing	Polycarbonate Self extinguishing
Method of fix	Brackets supplied	Brackets Supplied	Brackets Supplied	Brackets Supplied	Brackets Supplied	Brackets Supplied
Lamp holder cap	G5	G5	G5	G5	G5	G5
Lamp type	T5 Triphosphor 3500k	T5 Triphosphor 3500k	T5 Triphosphor 3500k	T5 Triphosphor 3500k	T5 Triphosphor 3500k	T5 Triphosphor 3500k
Electrical Connections	2mtr mains lead/socket	2mtr mains lead/socket	2mtr mains lead/socket	2mtr mains lead/socket	2mtr mains lead/socket	2mtr mains lead/socket
Running Gear / Make	Electronic	Electronic	Electronic	Electronic	Electronic	Electronic
Electrical Protection	Internal Fuse	Internal Fuse	Internal Fuse	Internal Fuse	Internal Fuse	Internal Fuse
F mark	Yes	Yes	Yes	Yes	Yes	Yes
CE mark	Yes	Yes	Yes	Yes	Yes	Yes
Quality Assurance System	ISO 9001	ISO 9001	ISO 9001	ISO 9001	ISO 9001	ISO 9001
Batch coding on product	Yes	Yes	Yes	Yes	Yes	Yes
Certificate of Conformity (Held on File)	Yes	Yes	Yes	Yes	Yes	Yes
Manufactured in accordance to:	EN60 598-2-5	EN60 598-2-5	EN60 598-2-5	EN60 598-2-5	EN60 598-2-5	EN60 598-2-5
Guarantee Period	1 Year	1 Year	1 Year	1 Year	1 Year	1 Year